

F-1707

1000V CAT II
600V CAT III

250 x 100 x 44 mm
450 g



FUNCTIONS	RANGE	RESOLUTION
DC Amps	$\frac{400A}{1000A}$	$\frac{0.1A}{1A}$
AC Amps	$\frac{400A}{1000A}$	$\frac{0.1A}{1A}$
DC Volts	$\frac{0.4V/4V/40V}{400V/1000V}$	$\frac{0.1mV/1mV/10mV}{0.1V/1V}$
AC Volts	$\frac{4V/40V/400V}{700V}$	$\frac{1mV/10mV/0.1V}{1V}$
Resistance	$\frac{400\Omega/4k\Omega/40k\Omega}{400k\Omega/4M\Omega/40M\Omega}$	$\frac{0.1\Omega/1\Omega/10\Omega}{0.1k\Omega/1k\Omega/10k\Omega}$
Capacitance	$\frac{4nF/40nF/400nF}{4\mu F/40\mu F}$	$\frac{1pF/10pF/0.1nF}{1nF/10nF}$
Frequency	$\frac{40Hz/400Hz/4kHz}{40kHz/100kHz}$	$\frac{0.01Hz/0.1Hz}{1Hz/10Hz/0.1kHz}$
Diode check	Yes	—
Continuity	Yes	—
Temperature	$\frac{400^{\circ}C \sim 750^{\circ}C}{0^{\circ}C \sim 400^{\circ}C}$ $-40^{\circ}C \sim 0^{\circ}C$	$\frac{1^{\circ}C}{1^{\circ}C}$ $1^{\circ}C$

CARACTERÍSTICAS:

- Pinza amperimétrica + multímetro digital.
- 1000 V CAT II / 600 V CAT III
- DC Volts: 0 V / 1000 V
- AC Volts: 0 V / 700 V
- DC Amps: 0 A / 1000 A
- AC Amps: 0 A / 1000 A
- Comprobación de diodos.
- Comprobación de continuidad.
- Temperatura: $-40^{\circ}C$ / $750^{\circ}C$
- Duty cycle: 0 % / 99 %
- Frecuencia: 0 Hz / 100 KHz
- Capacitancia: 4 pF / 40 μF
- Avisador acústico de continuidad
- Retención de lectura (HOLD)
- Display LCD
- Indicador de batería baja.
- Indicación de polaridad.
- Alimentación : 1 pila 9 V tipo 6F22
- Cumple las normas: CE, IEC 101, CAT II y CAT III
- Accesorios incluidos:
 - Sonda de temperatura.
- Manual de instrucciones totalmente ilustrado.
- Dimensiones: 250 x 100 x 44 mm
- Peso: 450 g

FEATURES:

- *Clamp meter + digital multimeter*
- *1000 V CAT II / 600 V CAT III*
- *DC Voltage: 0 V / 1000 V*
- *AC Voltage: 0 V / 700 V*
- *DC Current: 0 A / 1000 A*
- *AC Current: 0 A / 1000 A*
- *Diode test*
- *Continuity test*
- *Temperature: $-40^{\circ}C$ / $750^{\circ}C$*
- *Duty cycle: 0% / 99%*
- *Frequency: 0 Hz / 100 kHz*
- *Capacitance: 4 pF / 40 μF*
- *Audible continuity indicator*
- *Data hold function*
- *LCD display*
- *Low battery indicator*
- *Polarity indication*
- *Power supply: 1 x 9V 6F22 battery*
- *Complies with standards: CE, IEC 101, CAT II and CAT III*
- *Included accessories:*
 - *Temperature probe*
- *Fully illustrated instruction manual*
- *Dimensions: 250 x 100 x 44 mm*
- *Weight: 450 g*