

F-1708

600V CAT III

218 x 80 x 30 mm

400 g



FUNCTIONS	RANGE	RESOLUTION
DC Amps	$\frac{60A}{600A}$	$\frac{0.01A}{0.1A}$
AC Amps	$\frac{60A}{600A}$	$\frac{0.01A}{0.1A}$
DC Volts	$\frac{600mV/6V/60V}{600V}$	$\frac{0.1mV/0.001V/0.01V}{0.1V}$
AC Volts	6V/60V/600V	1mV/10mV/0.1V
Resistance	$\frac{600\Omega/6k\Omega/60k\Omega}{600k\Omega/6M\Omega/60M\Omega}$	$\frac{0.1\Omega/0.001K\Omega/0.01k\Omega}{0.1k\Omega/0.001M\Omega/0.01M\Omega}$
Capacitance	$\frac{6.6\mu F/66\mu F/660\mu F}{6.6mF/66mF}$	$\frac{0.001\mu F/0.01\mu F/0.1\mu F}{0.001mF/0.01mF}$
Frequency	660Hz/1KHz/>1KHz	0.1kHz/0.001KHz 0.001KHz
Diode check	Yes	—
Continuity	Yes	Built-in buzzer sounds when resistance is lower than 50
NCV	Frequency range 50Hz - 500Hz	Voltage range 90V - 1000V

CARACTERÍSTICAS:

- Pinza amperimétrica + multímetro digital.
- 600 V CAT III
- DC Volts: 0 V / 600 V
- AC Volts: 0 V / 600 V
- DC Amps: 0 A / 600 A
- AC Amps: 0 A / 600 A
- Comprobación de diodos.
- Comprobación de continuidad.
- Duty cycle: 0 % / 99 %
- Frecuencia: 0 Hz / 1 KHz
- Capacitancia: 6 pF / 66 mF
- NCV: 50 Hz - 500 Hz
- Avisador acústico de continuidad
- Retención de lectura (HOLD)
- Display retro-iluminado
- Iluminación LED en interior pinza
- Indicador de batería baja.
- Indicación de polaridad.
- Alimentación : 3 pilas 1,5 V tipo AAA
- Cumple normas: CE, IEC 101, CAT II y CAT III
- Manual de instrucciones totalmente ilustrado.
- Dimensiones: 218 x 80 x 30 mm
- Peso: 400 g

FEATURES:

- Clamp meter + digital multimeter
- 600 V CAT III
- DC Voltage: 0 V / 600 V
- AC Voltage: 0 V / 600 V
- DC Current: 0 A / 600 A
- AC Current: 0 A / 600 A
- Diode test
- Continuity test
- Duty cycle: 0% / 99%
- Frequency: 0 Hz / 1kHz
- Capacitance: 6 pF / 66 mF
- NCV: 50 Hz - 500 Hz
- Audible continuity indicator
- Data hold function
- Backlit display
- LED lighting inside the clamp
- Low battery indicator
- Polarity indication
- Power supply: 3 x 1,5V AAA
- Complies with standards: CE, IEC 101, CAT II and CAT III
- Fully illustrated instruction manual
- Dimensions: 218 x 80 x 30 mm
- Weight: 400 g