

F-1830

600V CAT III

138 x 69 x 31 mm
300 g



FUNCTIONS	RANGE	RESOLUTION
DC Volts	200mV/2V/20V 200V/600V	100μV/1mV/10mV 100mV/1V
AC Volts	200V 600V	100mV 1V
DC Amps	20μA/200μA/2mA 20mA/200mA/10A	0.01μA/0.1μA/1μA 10μA/100μA/10mA
Resistance	200Ω/2KΩ/20KΩ 200KΩ/2MΩ	0.1Ω/1Ω/10Ω 100Ω/1KΩ
Diode check	Yes	—
Continuity	Yes	—

CARACTERÍSTICAS:

- Multímetro digital de 3½ dígitos.
- 600 V CAT III
- DC Volts: 0 V / 600 V
- AC Volts: 0 V / 600 V
- DC Amps: 0 A / 10 A
- Ohms: 0 Ω / 2 MΩ
- Comprobación de diodos.
- Comprobación de continuidad.
- Avisador acústico de continuidad
- Retención de lectura (HOLD)
- Display retro-iluminado (Back light)
- Indicador de batería a baja
- Alimentación : 1 pila 9 V tipo 6F22
- Cumple las normas: CE, IEC 101, CAT III
- Protector de goma
- Dimensiones: 138 x 69 x 31 mm
- Peso: 300 g

FEATURES:

- Digital multimeter 3½ digits.
- 600V CAT III
- DC Voltage: 0V / 600V
- AC Voltage: 0V / 600V
- DC Current: 0A / 10A
- Ohms: 0Ω / 2MΩ
- Diode test
- Continuity test
- Audible continuity indicator
- Data hold function
- Backlit display
- Low battery indicator
- Power supply: 1 x 9V 6F22 battery
- Complies with standards: CE, IEC 101, CAT III
- Rubber protector
- Dimensions: 138 x 69 x 31mm•
- Weight: 300g