


F-2930

230 V ~ 50/60 Hz • 680 W

12 - 24 V
15 - 30 A



360 x 205 x 260 mm
16,700 kg



15-30A 12V
24V



DIGITAL VOLTMETER



AUTO - FUSE



CARACTERÍSTICAS:

- Cargador manual / automático y mantenedor.
- Tensión de la batería: **12 - 24 V**
- Intensidad: **15 - 30 A**
- Para baterías de plomo-ácido: líquidas, gel y AGM.
- Baterías recomendadas: de **105 a 360 Ah** de capacidad.
- Voltímetro digital.
- Controlado por microprocesador.
- Función test de batería y alternador.
- Función *Charge Restart*: En caso de interrupción de la corriente eléctrica, el cargador se reinicia cuando se restablece el suministro, conservando el último programa de carga seleccionado.
- Doble aislamiento.
- Con protector térmico rearmable.
- Potencia máxima consumida: 680 W
- Tensión de alimentación: 230 V ~ 50/60 Hz
- Dimensiones: 360 x 205 x 260 mm
- Peso: 16,700 kg

FEATURES:

- Manual/automatic charger and maintainer.
- Battery voltage: **12-24V**
- Intensity: **15-30A**
- For lead-acid batteries: liquid, gel and AGM.
- Recommended battery capacity: **105 to 360Ah**.
- Digital voltmeter
- Controlled by microprocessor.
- Battery and alternator test function.
- *Charge Restart* function: In case of interruption of the electrical current, the charger restarts when supply is restored, preserving the last selected charging program.
- Double insulation.
- With resettable thermal protector.
- Maximum power consumed: 680W
- Supply voltage: 230V ~ 50/60Hz
- Dimensions: 360 x 205 x 260mm
- Weight: 16.700g