

F-705

230 V ~ 50/60 Hz • 46 W

6 V - 12 V
1,5 - 3 A



150 x 90 x 135 mm
1,550 kg

1,5-3A 6V 12V



AMMETER



RESETTABLE FUSE



RESISTANT
METAL
HOUSING

CARACTERÍSTICAS:

- Cargador manual.
- Tensión de la batería: **6 - 12 V**
- Intensidad: **1,5 - 3 A**
- Baterías recomendadas: de **9 a 45 Ah** de capacidad.
- Amperímetro analógico.
- Para baterías de plomo-ácido.
- Función *Charge Restart*: En caso de interrupción de la corriente eléctrica, el cargador se reinicia cuando se restablece el suministro, conservando el último programa de carga seleccionado.
- Con protector térmico automático.
- Doble aislamiento.
- Potencia máxima consumida: 46 W
- Tensión de alimentación: 230 V ~ 50/60 Hz
- Dimensiones: 150 x 90 x 135 mm
- Peso: 1,550 kg

FEATURES:

- Manual charger
- Battery voltage: **6-12V**
- Intensity: **1,5-3A**
- For lead-acid batteries.
- Recommended battery capacity: **9 to 45Ah**.
- Analog ammeter
- *Charge Restart* function: In case of interruption of the electrical current, the charger restarts when supply is restored, preserving the last selected charging program.
- With automatic thermal protector.
- Double insulation.
- Maximum power consumed: 46W
- Supply voltage: 230V ~ 50/60Hz
- Dimensions: 150 x 90 x 135mm
- Weight: 1.550g