

F-807

230 V ~ 50/60 Hz • 210 W



12 - 24 V
4 - 8 A



210 x 125 x 180 mm
4,230 kg

4-8A

12V
24V



VOLTMETER



RESETTABLE FUSE



RESISTANT
METAL
HOUSING

CARACTERÍSTICAS:

- Cargador manual.
- Tensión de la batería: **12 - 24 V**
- Intensidad: **4 - 8 A**
- Baterías recomendadas: de **24 a 95 Ah** de capacidad.
- Amperímetro analógico.
- Función *Charge Restart*: En caso de interrupción de la corriente eléctrica, el cargador se reinicia cuando se restablece el suministro, conservando el último programa de carga seleccionado.
- Para baterías de plomo-ácido.
- Con protector térmico automático.
- Doble aislamiento.
- Potencia máxima consumida: 210 W
- Tensión de alimentación: 230 V ~ 50/60 Hz
- Dimensiones: 210 x 125 x 180 mm
- Peso: 4,230 kg

FEATURES:

- Manual charger
- Battery voltage: **12-24V**
- Intensity: **4-8A**
- For lead-acid batteries.
- Recommended battery capacity: **24 to 95Ah**.
- Analog ammeter.
- Charge Restart function: In case of interruption of the electrical current, the charger restarts when supply is restored, preserving the last selected charging program.
- With automatic thermal protector.
- Double insulation.
- Maximum power consumed: 210W
- Supply voltage: 230V ~ 50/60Hz
- Dimensions: 210 x 125 x 180mm
- Weight: 4.230 kg