


F-812

230 V ~ 50/60 Hz • 315 W

12 - 24 V
6 - 12 A



290 x 170 x 240 mm
8,620 kg

6-12A **12V
24V**



WITH HANDLE



DIGITAL VOLTMETER
AND AMMETER



AUTO - FUSE



RESISTANT
METAL
HOUSING

CARACTERÍSTICAS:

- Cargador manual.
- Tensión de la batería: **12 - 24 V**
- Intensidad: **6 - 12 A**
- Baterías recomendadas: de **35 a 140 Ah** de capacidad.
- Voltímetro/amperímetro digital.
- Función *Charge Restart*: En caso de interrupción de la corriente eléctrica, el cargador se reinicia cuando se restablece el suministro, conservando el último programa de carga seleccionado.
- Con función test de batería y alternador.
- Para baterías de plomo-ácido.
- Con protector térmico rearmable.
- Doble aislamiento.
- Potencia máxima consumida: 315 W
- Tensión de alimentación: 230 V ~ 50/60 Hz
- Dimensiones: 290 x 170 x 240 mm
- Peso: 8,620 kg

FEATURES:

- Manual charger
- Battery voltage: **12-24V**
- Intensity: **6-12A**
- For lead-acid batteries.
- Recommended battery capacity: **35 to 140Ah**.
- Digital voltmeter/ammeter.
- Charge Restart function: In case of interruption of the electrical current, the charger restarts when supply is restored, preserving the last selected charging program.
- With resettable thermal protector.
- Battery and alternator test function.
- Double insulation.
- Maximum power consumed: 315W
- Supply voltage: 230V ~ 50/60Hz
- Dimensions: 290 x 170 x 240mm
- Weight: 8.620 kg